




SWITCH FUNCTION	
POS. 1	POS. 2
	
OFF	(ON)
OPEN	1-2

(ON) = MOMENTARY



Ø16.00  
[.630 in]



PANEL CUTOUT  
MAX. PANEL THICKNESS 6.0mm

Ø18.00  
[.709 in]

Ø12.00  
[.472 in]



CIRCUIT: SPST

▲ BODY FINISH  
POLISHED FINISH  
STAINLESS STEEL

▲ FLAT ACTUATOR  
POLISHED FINISH  
STAINLESS STEEL

1.50 ± .50  
[.059 ± .020 in]

14.00 ± .50  
[.551 ± .020 in]

17.00 ± .50  
[.669 ± .020 in]

.50  
[.020 in]

8.50  
[.335 in]

2.00  
[.079 in]

.80  
[.031 in]

M16x1.0

NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X±0.4  
X.XX±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: SILVER
5. RATING: 2A 48VDC
- ▲ 6. TRAVEL: 1.5 ± 0.2mm
7. ELECTRIC LIFE: 200,000 MAKE-AND-BREAK CYCLES
8. INSULATION RESISTANCE: 1,000 MΩ MIN.
9. DIELECTRIC STRENGTH: 2,000 VAC MIN. FOR 1 MINUTE
10. CONTACT RESISTANCE: 50mΩ MAX. @ 1A 12VDC
11. OPERATING TEMP.: -20°C to 55°C
12. ▲ DENOTES CRITICAL PARAMETER.
13. INGRESS PROTECTION: IP65
- ▲ 14. HARDWARE SUPPLIED: O-RING AND HEXNUT
15. 2002/95/EC (ROHS) COMPLIANT



TITLE PV2F240SS

C	20337	REVISED AND REDRAWN	12/13/11	BGL
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
2:1	12/13/2011	BGL	52-PV2F240SS	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED