



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

Rosenberger 28K000-000, series QMA
Rosenberger is an authorised QLF® manufacturer

Documents

Assembly instruction 28 A
Panel piercing B 57

Material and plating

Connector parts

Center contact
Outer contact
Body
Dielectric
Gasket

Material

CuBe
Brass
Brass
PTFE
Silicone

Plating

AuroDur®, gold plated
AuroDur®, gold plated
AuroDur®, gold plated

Electrical data

| | |
|---|---|
| Impedance | 50 Ω |
| Frequency | DC to 18 GHz |
| Return loss | ≥ 32 dB, DC to 3 GHz ≥ 25 dB, 3 to 6 GHz |
| Insertion loss | ≤ 0.05 x √f(GHz) dB, DC to 6 GHz |
| Insulation resistance | ≥ 5 x10 ³ MΩ |
| Center contact resistance | ≤ 3 mΩ |
| Outer contact resistance | ≤ 2.5 mΩ |
| Test voltage, at sea level, 50Hz | 1000 V rms |
| Working voltage, at sea level, 50Hz | 250 V rms |
| RF-leakage | ≥ 95 dB up to 2 GHz ≥ 80 dB up to 4 GHz ≥ 70 dB up to 6 GHz |
| Intermodulation (3 rd order) | ≤ -120 dBc |

- Limitations are possible due to the used cable type -

Mechanical data

| | |
|-----------------------------------|-----------|
| Mating cycles | min. 100 |
| Center contact captivation: axial | ≥ 20 N |
| Engagement force | typ. 25 N |
| Disengagement force | typ. 20 N |
| Retention force for interface | 60 N min. |

Environmental data

| | |
|-------------------------|--------------------------------|
| Temperature range | -40°C to +85°C |
| Storage temperature | -40°C to +85°C |
| Thermal shock | IEC 60169-1 16.4 (-40 / +85°C) |
| Corrosion | IEC 60169-1 16.7 (48 hrs) |
| Vibration | IEC 60068-2-64 random |
| Damp heat, steady state | IEC 60169-1 16.3 (96 hrs) |
| RoHS | compliant |

Tooling

N/A

Suitable cables

UT 85, RG 405

Weight

Weight 4.9 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|--|----------|-------------------|----------|------|--|-----------|---------------|
| A. König | 05/10/04 | Sa. Krautenbacher | 13.03.14 | e00 | 14-0352 | T. Krojer | 13.03.14 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de | | Page 2 / 2 |