

## THIS CONNECTOR IS COVERED BY U.S. PATENT 3,336,563

## MIL-C-39012 INSPECTION

## 

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0.381 mm) ±.005 (0.127 mm) ± 1°	MATERIAL	DRAWN PADMANABHAN E	DATE 07-Jul-09	TITLE BNC STR PLUG MI	- (
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	- SEE NOTES	ENGINEER PADMANABHAN E	DATE 07 - Jul - 09	(CATEGORY C) F(	OR RO
	REFERENCE MIL-C-39012/16-0013	APPROVED	DATE	4  & 303 CABLE	
	CONFIGURATION LEVEL: In Work	K. CAPOZZI	6/1/16	SCALE: 5.5:1.0 SHEET 2	2 OF 2
		CAD FILE		DWG SIZE	
	FINISH			В	

RF	VISIONS				
RIPTION			DATE	ECO	APPR
E TO MFG.					 DNE
E, COD SHEE F UPDATED	LI ADDED		4-Jan- 3 09-May- 6	48616	P N E M R
OR UPDATED	i		5/1/16	00883	MR
		~			
					$\frown$
-					
_	$\overline{}$		J. S.		
	/		SCAL	E 2.000	
	,				
	2				
LE NS					
<u></u>					
				_	
					-
				- Ø0.1	206
				<u> </u>	
	\F	ERRULE			
MER	OUT				ING
OTHER SHE	ETS ARE F				
-CRIMP	/	Amph	enol	Κŀ	
RG 58, www.amphenolrf.com					
	DRAWING	NO.31	-4320		
F2 REV	ITEM NO				
W	PART NO	. 3   - 4 3	20		